

TORO**Count on it.**

Workman® MD/MDX/MDE

F E A T U R E S

- SRQ™ (Superior Ride Quality):
 - Front suspension Independent A-Frame™ design with coil-over shock absorbers (All models)
 - Rear suspension Swing Arm design with coil-over shocks (MD & MDX models)
- Patented Active in Frame™ twister pivot joint for enhanced stability and traction
- The capacity to get more jobs done in less time:
 - 1,200 lb total capacity – MDE
 - 1,250 lb total capacity – MD
 - 1,650 lb total capacity – MDX

Power and productivity to tackle the toughest jobs...

...but the hard work shouldn't start until you get to the job site.

The new Workman® MD Series with SRQ™ combines a coil-over shock absorber suspension design with an Active In Frame™ twister joint.

These features deliver superior ride quality for optimum operator comfort.

The hefty payload capacity and four-wheel hydraulic brakes combine with SRQ to provide enhanced productivity and exceptional operator control.

Experience the Workman MD Series with SRQ. The better way to get your job done.



- Four-wheel hydraulic brakes for authoritative stopping power
- Extended run batteries and regenerative braking for a longer per charge work capacity and whisper-quiet operation (MDE model)
- New injection-molded body styling
- Proven durability of steel diamond plate floorboard, rotomolded plastic bumper, dash and cargo bed

Call your Toro distributor at 1-800-803-8676

Workman® MD/MDX Specifications



	Workman MD	Workman MDX	
Engine	12 hp (9 kW), 357 cc, air-cooled, single-cylinder, Kohler® Command Pro™	14 hp (11.9 kW), 480 cc, air-cooled, 2-cylinder, Briggs and Stratton® Vanguard®	
S.R.Q. System	Active In-Frame™ twister pivot joint, front and rear suspension.		
Front Suspension	Independent "A"-Frame with coil over shock absorbers.		
Rear Suspension	Trailing arm with coil over shock absorbers.		
Maximum Speed	15-16 mph (24.1-25.6 km/h) governed.	16 mph (25.6 km/h) governed.	
Brakes	Four wheel hydraulic disc. Rear wheel hydraulic drum.		
Frame	Welded steel channel and tube in body construction. Frame surfaces are dipped in e-coat. Body and bed constructed of dent and corrosion resistant polyethylene.		
Ground Clearance	Front: 10" (25.4 cm), Rear: 7" (18 cm)		
Tires	Front: 22 x 9.5-10, 4-ply, Rear: 22 x 9.5-10, 4-ply	Front: 22 x 9.5-10, 4-ply, Rear: 24 x 12-10, 4-ply.	
Fuel Capacity	7 gallons (26.5 liters)		
Dimensions	Width 59" (150 cm)	Length 117.75" (299 cm)	Wheel Base 81" (205.7 cm)
Steering	Manual, pinion and sector gear system with ergonomically positioned non-adjustable column. Steering wheel has 3 turns lock-to-lock and 17.2 to 1 ratio with a 13.75" (34.93 cm) diameter wheel.		
Turning Clearance Circle	Inside rear tire: 87" (221 cm), outside front tire: 257" (653 cm).		
Instrumentation/Dash	Hour meter, low oil pressure warning light, accessory power port. Dash has 2 cup holders, radio holder and glove box storage.		
Cargo Bed Size	Length: 49" (124 cm), Width: 52" (132 cm), Height: 10" (25 cm), double walled, polyethylene plastic.		
Total Capacity	1,250 lbs. (567 kg)	1,650 lbs. (750 kg)	
Cargo Bed Capacity	850 lbs. (386 kg)	1,250 lbs. (567 kg)	
Trailer Towing Capacity	400 lbs. (182 kg) trailer, 50 lbs. (23 kg) tongue weight with standard hitch. 800 lbs. (363 kg) trailer, 100 lbs. (45 kg) tongue weight with heavy-duty tow hitch.	400 lbs. (182 kg) trailer, 50 lbs. (23 kg) tongue weight with standard hitch. 1200 lbs. (545 kg) trailer, 100 lbs. (45 kg) tongue weight with heavy-duty tow hitch.	
Optional Accessories	Canopy, Solid & Folding Windshield, Electric Bed Lift, HD Bumper, Brush Guard, Rahn® Groomer, ROPS, Brake/Tail/Signal Light Kit, Stake Sides, Deluxe Cab, Snow Plow, Deluxe Refreshment Center, Portable Refreshment Center, Slant Board, Heater Kit, HD Trailer Hitch, Rear Lift Kit.		
Warranty	Two-year or 1,500 hour limited warranty. Refer to the Operator's Manual for further details.		

Workman® MDE Specifications



Workman MDE

Motor	48 volt DC motor with external fan.			
S.R.Q. System	Active In-Frame™ twister pivot joint, front suspension.			
Front Suspension	Independent "A"-Frame with coil over shock absorbers.			
Maximum Speed	16 mph (25.6 km/h) with fully charged batteries. Economy/supervisor mode limits maximum speed to 12 mph (19.2 km/h).			
Brakes	Front wheel: hydraulic disc, Rear wheel: hydraulic drum. Complemented with regenerative braking.			
Transaxle	16.99 to 1 ratio with helical gears. Direct drive double reduction with differential.			
Ground Clearance	Front: 10" (25.4 cm), Rear: 7" (18 cm)			
Tires	Front: 22 x 9.5-10, 4-ply, Rear: 22 x 9.5-10, 4-ply			
Batteries	Eight 6 volt heavy-duty T145. 145 min. @ 75 amps.			
Controller	500 amps max. 48 volt with regenerative braking, includes roll away indicator, thermal cutback, sealed/potted, status indicator light.			
Charger	Remote charger with drive inhibit on AC connect. 115 volt AC +/- 10% input, 48 volt DC (nominal) 17 amp output. 230 volt AC input for Europe, 48 volt DC (nominal) 17 amp output.			
Instrumentation/Dash	Battery discharge indicator, hour meter, headlight switch, on/off ignition key switch, supervisor speed selector switch. The dash has 2 cup holders, radio holder and glove box storage area. Accessory power port.			
Dimensions	Width	Length	Wheel Base	Height
	59" (150 cm)	119.75" (304 cm)	83" (211 cm)	50" (127 cm)
Steering	Manual, pinion and sector gear system with ergonomically positioned non-adjustable column. Steering wheel has 3 turns lock-to-lock and 17.2 to 1 ratio with a 13.75" (34.93 cm) diameter wheel.			
Turning Clearance Circle	Inside rear tire: 83" (211 cm), outside front tire: 260" (660 cm).			
Frame	Welded steel channel and tube in body construction. Frame surfaces are dipped in e-coat. Body and bed constructed of dent and corrosion resistant polyethylene.			
Cargo Bed Size	Length: 49" (124 cm), Width: 52" (132 cm), Height: 10" (25 cm), double walled, polyethylene plastic.			
Total Capacity	1,200 lbs. (545 kg)			
Cargo Bed Capacity	800 lbs. (363 kg)			
Trailer Towing Capacity	400 lbs. (182 kg) trailer, 50 lbs. (23 kg) tongue weight with standard hitch. 800 lbs. (363 kg) trailer, 100 lbs. (45 kg) tongue weight with heavy-duty tow hitch.			
Optional Accessories	48 volt Bed Lift, 48 volt Rear Lift, Canopy, Folding/Solid Windshield, HD Trailer Hitch, Deluxe Cab, HD Front Bumper, Brush Guard, Stake Sides, Portable Refreshment Center, Rahn® Groomer, 12 volt Adapter Kit, Slant Board, ROPS, Brake/Tail/Signal Light Kit.			
Warranty	Two-year or 1,500 hour limited warranty. Refer to the Operator's Manual for further details. Battery warranty through battery manufacturer.			